

Zircon



ZIRCON
Allow your coffee to sparkle



Designed for any location

The Zircon range consists of a group of well-known espresso machines in a wide range of models. From the basic model to more advanced appliances with many features. Regardless of model, you can be assured that all are built using our class-leading technology. In other words, you are guaranteed machines of the highest quality that simplifies the barista's work.

The Zircon Integral machine consists of a one or two group model from our standard Zircon espresso machine, but now with the added benefit of a professional, integrated grinder, making this range even more practical when space is at a premium.

Together with the bespoke choices and the stylish design, the experience of the Zircon range is complete.

Features

- Built-in volumetric motor pump, equipped with two retention valves and solid particle filter
- Copper boiler with pressure relief valve
- Boiler dRAINTAP (except compact)
- Group head with direct pre-infusion chamber
- One steam arm and one hot water tap one group versions
- Two steam arms and one hot water tap in all 2 & 3 group models
- Element overheat protection
- Low water auto cut-off
- Inbuilt back-flush function

Integral Grinder

- Automatic grinder
- 1 kilo bean hopper
- 60mm diameter burrs
- Powerful 445w 1300 rpm motor with thermal protection
- Adjustable dose from 5 to 12g

Supplied Accessories

- 1 single portafilter all machines
- 1 group, 1 double portafilter
- 2 group, 2 double portafilters
- 3 group, 3 double portafilters
- 0.55 metre water filter hose
- 1.5 metre waste hose
- 1 cleaning membrane
- 1 espresso cup stand

Optional Accessories

- Capsule conversion kits
- Under machine knock out drawer for integral versions



Details



Variants



1 Group



2 Group Compact



2 Group



3 Group



1 Group Integral Grinder



2 Group Integral Grinder

Specifications	1 group	2 group compact	2 group	3 group single phase
Height	20.86 in / 530mm	20.86 in / 530mm	20.86 in / 530mm	20.86 in / 530mm
Depth	23.22in / 590mm	23.22in / 590mm	23.22in / 590mm	23.22in / 590mm
Width	18.11 in / 460mm	18.11 in / 460mm	27.16 in / 680mm	38.58 in / 980mm
Weight	79 lb / 36 kg	88 lb / 40 kg	121 lb / 55 kg	160 lb / 73 kg
Brewing Groups	1	2	2	3
Boiler Volume (Litre)	6	6	11.5	17.5
Boiler Pressure (Bar)	0.8 to 1.2	0.8 to 1.2	0.8 to 1.2	0.8 to 1.2
Total Boilers	1	1	1	1
Steam Wands	1	2	2	2
Hot Water Tap	1	1	1	1
Integral Grinder	No	No	No	No
Noise Level	<70dB	<70dB	<70dB	<70dB
Power Supply	220-240VAC, 50/60Hz, 1N-2770W	220-240VAC, 50/60Hz, 1N-2780W	220-240VAC, 50/60Hz, 1N-3330W	220-240VAC, 50/60Hz, 1N-4290W
Water Connection	G3/8 Internal thread	G3/8 Internal thread	G3/8 Internal thread	G3/8 Internal thread

	3 group three phase	1 group integral	2 group integral
Height	20.86 in / 530mm	24.86 in / 690mm	24.86 in / 690mm
Depth	23.22in / 590mm	23.22in / 590mm	23.22in / 590mm
Width	38.58 in / 980mm	18.11 in / 460mm	27.16 in / 680mm
Weight	160 lb / 73 kg	103 lb / 47 kg	121 lb / 55 kg
Brewing Groups	3	1	2
Boiler Volume (Litre)	17.5	6	11.5
Boiler Pressure (Bar)	0.8 to 1.2	0.8 to 1.2	0.8 to 1.2
Total Boilers	1	1	1
Steam Wands	2	1	2
Hot Water Tap	1	1	1
Integral Grinder	No	Yes	Yes
Noise Level	<70dB	<70dB	<70dB
Power Supply	380-415VAC, 50/60Hz, 3N-6330W	220-240VAC, 50/60Hz, 1N-3150W	220-240VAC, 50/60Hz, 1N-3685W
Water Connection	G3/8 Internal thread	G3/8 Internal thread	G3/8 Internal thread



Welbilt offers fully-integrated kitchen systems and our products are backed by KitchenCare[®] aftermarket parts and service. Welbilt's portfolio of award winning brands includes **Cleveland[™]**, **Convotherm[®]**, **Crem[®]**, **Delfeld[®]**, **ftkitchen[®]**, **Frymaster[®]**, **Garland[®]**, **Kolpak[®]**, **Lincoln[™]**, **Manitowoc[®]**, **Merco[®]**, **Merrychef[®]** and **Multiplex[®]**.

Bringing innovation to the table • welbilt.com